



CHATWANE



SHT Series

Ventilation Fans



Product Description

- ❖ Ventilator shell: made of hot-dipped galvanized sheet which has spray painted automobile coating on its surface
- ❖ Impeller: made of aluminum casting alloy blades.
- ❖ Fan guard: dusting, zinc coating
- ❖ Switch: Push button.
- ❖ Integrated plastic handle for easy carrying.
- ❖ Motor: It is wrap around with international standard copper wire
- ❖ With radiating rib aluminum casting integrated motor shell.

Technical parameters

Model No.	Diameter	Voltage	Phase	Frequency	Speed	Power	Air Flow	Static	Noise
SHT	mm	v		Hz	rpm	W	m3/min	pa	dB(A)
SHT-20	200(8")	220	1	50/60	2800	230	25	245	63
SHT-25	250(10")	220	1	50/60	2800	320	43	294	68
SHT-30	300(12")	220	1	50/60	2800	520	65	373	71
SHT-40	400(16")	220	1	50/60	2800	1100	96	700	80
SHT-50	500(20")	220	1	50/60	2800	1500	200	1050	88
SHT-60	600(24")	220	1	50/60	1400	1500	240	1100	92

Application

- ❖ Exhaust and supply fresh air in remote or deep operating zone, confined space construction and other bad air environment.
- ❖ Exhausting welding waste gas, smoke, dust, the smell of paint during shipbuilding and maintenance.
- ❖ Field of machinery, chemical industry, plant warehouse, underground sinking and driving engineering

LINE ID



Tel. 065-359-6297 Mail: ctffans@gmail.com