

**Fiber Glass Farm Fans** 





**FRP Series** 



## **Product Description**

- High air performance; Energy-efficient & extremely low noise level; direct drive and a very stable connection between hub and blades for easy maintenance. Fan body is made of high-quality FRP that preventing corrosion. The blades have passed balance test, stable performance, big volume, and low noise.
- Parallel flow theory made PVC shutters, can stop the flies, and prevent the air flow back.
- High performance low speed motor, good quality, long life time.

С Н

WANE

The fan is widely used in poultry and industry, to exhaust NH3, H2S waste air and damp air, exhaust hot air, smoke, dust, etc.

## **Technical parameters**

| Model  | Diameter    | Voltage | Frequency | Blade<br>Speed | Power | Air Flow | Dimension         |
|--------|-------------|---------|-----------|----------------|-------|----------|-------------------|
|        | mm / Inches | V       | Hz        | rpm            | w     | m³/h     | mm X mm X mm      |
| FRP-24 | 630(24")    | 380     | 50/60     | 930            | 370   | 12,600   | 850 X 850 X 500   |
| FRP-36 | 920(36")    | 380     | 50/60     | 560            | 550   | 24,000   | 1060 X 1060 X 550 |
| FRP-50 | 1270(50'')  | 380     | 50/60     | 560            | 1100  | 45,500   | 1460 X 1460 X 600 |



Tel. 065-359-6297

Mail: ctffans@gmail.com



